## InstaShow™ (Button Kit) General Specifications

Color	Black
Support Platform	Windows, MAC, Chrome. Any OS supports HDMI standard 1.4
Video Outputs	HDMI 1.4, comply with HDCP
Frame Rate	Up to 30 fps depending on environment
Output Resolution	800 x 600, 1280x720 (720P),1024 x 768 (XGA),1280 x 768,1280x800(WXGA),1280 x 1024,1280 x 960,1360 x 768,1440 x 900,1400 x 1050,1680 x 1050, 1920x1080 (1080p)
Input Resolution	Up to 1920x1080
Simultaneous Connections	16 pcs
Audio	Stereo, Radio quality 16 bits 48KHz

<b>USB Extended Cable</b>	x1 (15cm), x1 (80cm)
InstaShow Button	x2
InstaShow Package	
Humidity	Storage: 5% to 90% relative humidity, non-condensing Operation: 10% to 80% relative humidity, non-condensing
Temperature Range	Operating: 0°C to +40°C (+32°F to +104°F) Storage: -10°C to +60°C (+14°F to +140°F)
Reach	Max. 8m between InstaShow Button and InstaShow Host
Security (encryption )	AES 128 bit
Authentication Protocol	WPA2 (WPA2-PSK (Pre-Shared key) / WPA2-Enterprise)
Data Rate Wireless	Up to 400Mbps
Wireless	IEEE 802.11ac, 5GHz, 2T2R

Safety Statement	x 1
Cradle	<b>x1</b>
Quick Start Guild	<b>x1</b>
InstaShow Button	
Cable	USB Type A, HDMI Cable
Reset Button	<b>x1</b>
Mode Key	<b>x1</b>
LED	*Red (boosting), Green (wifi connected), Blue (presenting)
Power Supply	DC 5V±10%, 0.9A
Power Consumption	Normal: 4.5W
Dimensioin (WxHxD)	84.5 x 189.55 x 19.9mm

## Notes

<sup>\*</sup>InstaShow Button is activated when paired with InstaShow Host.

<sup>\*\*</sup>Please find detail LED behavior in the user manual.

<sup>\*\*\*</sup>Wireless connection speed depends on wireless environment.