

JBL AW266 Specs

Driver	Low Frequency Driver: 1 x JBL 2262H 12" (300 mm) Differential Drive driver with 3" (75 mm) dual voice coil High Frequency Driver: JBL 2432H 1.5" (38 mm) exit compression driver with 3" (75 mm) voice coil
Crossover Frequency	1.1 kHz
Frequency Range	40 Hz - 20 kHz
Frequency Response ± 3dB	51 Hz - 18 kHz
Coverage Pattern	60 x 60°
Directivity Factor	15.8
Directivity Index	12 dB
Impedance	8 ohms
Long-Term System Power Rating	500 W (200 W peak), 100 hours
Sensitivity	System: 98 dB LF Driver: 96 dB SPL HF Driver: 113 dB SPL
Maximum Sound Pressure Level (SPL)	126 dB

Transformer Taps	70 V: 400 W, 200 W, 100 W >br> 100 V: 400 W, 200 W
Connectors	Barrier strip terminals
Enclosure Material	Hand-laminated fiberglass
Dimensions (HxWxD)	16.1 x 28.8 x 17.8" / 409.0 x 732.0 x 452.0 mm (in horizontal cabinet orientation)
Weight	55.5 lb / 25.2 kg

Packaging Info

Package Weight	71.4 lb
Box Dimensions (LxWxH)	32 x 20 x 19"