

JBL C24CT MICROPLUS Specs

Speaker

Active or Passive	Passive
Speaker Configuration	2-Way
Constant Voltage / Transformer Taps	100 V: 12 / 25 W 70 V: 6 / 12 / 25 W
Shielded	No

Drivers

HF Driver	0.5" / 1.2 cm Polycarbonate Tweeter
LF Driver	4.5" / 11.5 cm Graphite Woofer
LF Voice Coil	1" / 2.4 cm

Performance

Frequency Range	80 Hz to 25 kHz -10 dB
Maximum SPL	99 dB

Sensitivity	85 dB SPL
Coverage Angle	150° H x 150° V
Crossover	3.5 kHz, 18 dB/Octave

Connectivity

I/O Connectors	Screw Terminal
----------------	----------------

Environmental

Certifications	UL, as per Manufacturer
----------------	-------------------------

Physical

Color	White
Cutout Depth	4.1" / 10.5 cm
Cutout Size	6.6" / 16.7 cm
Construction Material	Medium-Impact Polystyrene, Steel
Dimensions	7.7 x 5.2" / 19.5 x 13.3 cm
Weight	5.5 lb / 2.5 kg

Packaging Info

Package Weight 15.9 lb

Box Dimensions (LxWxH) 25.5 x 10.8 x 7.4"
