

JBL 226CT Specs

Active or Passive	Passive
LF Driver	6.5" / 16.5 cm Kevlar-Reinforced Cone
HF Driver	1" / 2.5 cm Exit Titanium Compression Driver
Frequency Range	47 Hz to 19 kHz (-10 dB)
Frequency Response	74 Hz to 17 kHz (± 3 dB)
Coverage Pattern	120° Conical, Broadband
Directivity Factor	6 (1 to 16 kHz)
Directivity Index	7.9 dB (1 to 16 kHz)
Power Capacity	For 2 Hours: 150 W (600 W Peak) For 100 Hours: 100 W (400 W Peak)
Sensitivity	Measured Half-Space: 90 dB (2.83 V at 1 m) Computer for Competitive Comparison: 95 dB (2.83 V at 1 m)
Maximum SPL	Continuous: 112 dB Peak: 118 dB
Nominal Impedance	Bypass Mode: 8 Ohms

Transformer Taps	Watts at 70 V: 8.5, 17, 34, 68 Watts at 100 V: 17, 34, 68
Crossover	Frequency: 2.2 kHz Low-Pass Filter to LF Driver: 3rd Order (18 dB/Octave) High-Pass Filter to HF Driver: 3rd Order (18 dB/Octave)
Input	2 x Removable Locking 2-Pin Connectors with Screw-Down Terminals
Maximum Wire Gauge	12 AWG
Shielded	No
Cutout Size	12.1" / 30.7 cm
Dimensions (Diam. x Depth)	13.0 x 9.7" / 33.0 x 24.6 cm (from Back of Baffle)
Weight	20 lb / 9.1 kg
Safety Rating	UL 1480, UL 2043, NFPA 90, NFPA 70, S7232/UL, UL 1876, IEC 60849 / EN 60849

Packaging Info

Package Weight	49.5 lb
Box Dimensions (LxWxH)	30 x 17 x 14"