

JBL CBT 70J-1 Specs

Active or Passive

Passive

Frequency Response

60 Hz - 20 kHz

Power Capacity

500 W (2000 W Peak), 2 Hours
350 W (1400 W Peak), 100 Hours

Maximum Sound Pressure Level (SPL)

Narrow:

Speech Mode: 125 dB Continuous, 131 dB Peak

Music Mode: 120 dB Continuous, 126 dB Peak

Broad:

Speech Mode: 123 dB Continuous, 129 dB Peak

Music Mode: 119 dB Continuous, 125 dB Peak

Nominal Sensitivity

Narrow:

Speech Mode: 98 dB (1 kHz - 8 kHz)

Music Mode: 93 dB (300 Hz - 18 kHz)

Broad:

Speech Mode: 96 dB (1 kHz - 8 kHz)

Music Mode: 92 dB (300 Hz - 18 kHz)

Impedance

8 ohms

Crossover

Not Specified by Manufacturer

Low Frequency Driver

Four 5" (130 mm) Drivers, Dual Magnet Neodymium, 1.5" (38 mm) Voice Coil, Damped Blended Textile Surround, Coated Diaphragm for

Moisture, UV, and Salt Resistance,
Shielded

High Frequency Driver

Sixteen 1" (25 mm) Drivers, Dual
Magnet Neodymium, Encased
Magnet and Coated Diaphragm for
Moisture, UV and Salt Resistance,
Shielded

Enclosure Material

Fiberglass Reinforced ABS Cabinet,
Painted Aluminum Grille

Input Connections

Speaker Wire Terminals

Compliance

IP-54 rated per IEC529
UV, moisture and salt-spray resistant

Dimensions (HxWxD)

27.4 x 6.7 x 9.3" (69.4 x 17.0 x 23.7
cm)

Weight

21.0 lb (9.5 kg)

Packaging Info

Package Weight

31.8 lb

Box Dimensions (LxWxH)

36.5 x 13.5 x 12.8"
