

JBL PD5122 Specs

PA Speaker

Configuration	Passive
Enclosure Type	Bandpass Subwoofer
Total Power Capacity	Passive: 4800 W Peak (at 4 Ohms)
Amplifier Power Rating	1 x 4800 W Peak (at 4 Ohms)
System Impedance	2 x 8 Ohms (Discrete) 1 x 4 Ohms (Passive)

Drivers

LF Driver	2 x 12" / 304.8 mm Woofer
LF Voice Coil	4" / 101.6 mm

Performance

Frequency Range	41 Hz to 1 kHz -10 dB
Frequency Response	49 Hz to 300 Hz \pm 3 dB

Maximum SPL	134 dB SPL
-------------	------------

Speaker Sensitivity	96 dB SPL
---------------------	-----------

Connectivity

Audio I/O	1 x 4-Core Cable NL4 Speaker Input (Lockable) 1 x Barrier Strip 8-Pole Speaker Input/Thru
-----------	--

Physical

Mounting	20 x M10 (Bottom, Each Side, Rear, Top)
----------	--

Construction Material	Plywood
-----------------------	---------

Dimensions	14.8 x 26.2 x 27.8" / 375.9 x 665.5 x 706.1 mm
------------	--

Weight	80 lb / 36.3 kg
--------	-----------------

Packaging Info

Package Weight	109 lb
----------------	--------
