

JBL PD5125 Specs

PA Speaker

Configuration	Passive
Enclosure Type	Bass-Reflex Subwoofer
Total Power Capacity	Passive: 8000 W Peak (at 4 Ohms)
Amplifier Power Rating	1 x 8000 W Peak (at 4 Ohms)
System Impedance	2 x 8 Ohms (Discrete) 1 x 4 Ohms (Parallel)

Drivers

LF Driver	2 x 15" / 381 mm Woofer
LF Voice Coil	4" / 101.6 mm

Performance

Frequency Range	37 Hz to 2.5 kHz -10 dB
Frequency Response	42 Hz to 2.1 kHz \pm 3 dB

Maximum SPL	142 dB SPL
-------------	------------

Speaker Sensitivity	103 dB SPL
---------------------	------------

Connectivity

Audio I/O	1 x 4-Core Cable NL4 Speaker Input (Lockable) 1 x Barrier Strip 8-Pole Speaker Input/Thru
-----------	--

Physical

Mounting	20 x M10 (Bottom, Each Side, Rear, Top)
----------	--

Construction Material	Plywood
-----------------------	---------

Dimensions	39 x 18.8 x 27.2" / 990.6 x 477.5 x 690.9 mm
------------	--

Weight	118 lb / 53.5 kg
--------	------------------

Packaging Info

Package Weight	127 lb
----------------	--------

Box Dimensions (LxWxH)	41.5 x 33.5 x 31"
------------------------	-------------------
