

# Soundcraft Si Mini Stagebox 16iSpecs

Digital Connectivity	1 x MADI over RJ45/Cat5
Analog Inputs and Outputs	Remote-controlled mic preamps and A/D converters: 16 XLR Analog Line-Level Outputs: 8 x XLR
Maximum Distance	328.1' / 100.0 m
Frequency Response	Mic/Line Input to Any Output: +0/-1 dB, 20 Hz to 20 kHz
THD	Mic Sensitivity -30 dBu: < 0.01% @ 1 kHz
Residual Noise	-85 dBu
Mic Input Noise (E.I.N.)	-125 dBu (150 $\Omega$ source)
CMRR	Mix Noise, Masters at Unity: < -86 dBu 1 Input to Mix at Unity Gain: -84 dBu CMRR Mic @1 kHz (Max Gain): -86 dBu
Crosstalk	< -80 dB @ 1 kHz
Input Gain	-5 to 58 dB integrated pad design (1 dB steps)

Maximum Input Level	+24 dBu
Maximum Output Level	+22 dBu
Sample Rate	48 kHz
Converter	24-bit
Latency	1.5 ms
Clock Accuracy	±25 ppm
Power Consumption	33 W
Operating Range	90 to 264 VAC, 47 to 63 Hz
Operating Temperature Range	14 to 122°F (-10 to +50°C)
Relative Humidity	0 to 90%
Storage Temperature Range	14 to 122°F (-10 to +50°C)
Dimensions (W x H x D)	Not specified by manufacturer
Weight	Not specified by manufacturer

## Packaging Info

---

Package Weight 13.3 lb

---

Box Dimensions (LxWxH) 21.2 x 16.7 x 9.7"

---