

AKG C414 XLS Specs

Microphone

Polar Pattern	Cardioid, Figure-8, Hypercardioid, Omnidirectional, Wide-Angle Cardioid
---------------	---

Pattern Selection	Switched
-------------------	----------

Pad	-6 dB -12 dB -18 dB
-----	---------------------------

High-Pass Filter	40 Hz 80 Hz 160 Hz
------------------	--------------------------

Performance

Frequency Range	20 Hz to 20 kHz
-----------------	-----------------

Maximum SPL	140 dB SPL
-------------	------------

Impedance	200 Ohms
-----------	----------

Load Impedance	2200 Ohms
----------------	-----------

Sensitivity	23 mV/Pa
-------------	----------

Signal-to-Noise Ratio	88 dB A-Weighted
-----------------------	------------------

Equivalent Noise Level	6 dB A-Weighted
------------------------	-----------------

Connectivity

Output Connectors	1 x XLR 3-Pin
-------------------	----------------------

Power

Operating Voltage	44 to 52 V 48 V
-------------------	--------------------

Operating Current Consumption	4.5 mA
-------------------------------	--------

Physical

Operating Temperature	14 to 140°F / -10 to 60°C
-----------------------	---------------------------

Dimensions	ø: 1.97 x L: 6.3" / ø: 50 x L: 160 mm
------------	---------------------------------------

Weight	10.58 oz / 300 g
--------	------------------

Packaging Info

Package Weight 4.24 lb

Box Dimensions (LxWxH) 11.3 x 9.45 x 5.4"
