

# Mackie CR3-XBT Specs

## Studio Monitor

---

Monitor Type	Active 2-Way
Enclosure	Bass-Reflex
Power Rating	50 W Peak
Drivers	LF Driver: <b>1 x</b> 3" / 7.62 cm Polypropylene Cone HF Driver: <b>1 x</b> 0.75" / 1.91 cm Silk Dome
Amplification	<b>1 x</b> Full-Range Amplifier: Class-D50 W Peak

---

## Performance

---

Frequency Range	70 Hz to 20 kHz (at -10 dB) 80 Hz to 20 kHz (at -3 dB)
Maximum Sound Pressure Level (SPL)	97 dB
Phase Adjustment	<i>None</i>

---

## Signal Processing

---

EQ *None*

---

Filters *None*

---

Parametric EQ *None*

---

## Crossover

---

Crossover Frequency 3 kHz

---

## Connectivity

---

I/O

- 2 x** 1/4" TRS Balanced/Unbalanced Female Analog Input
- 1 x** 2RCA Unbalanced Female Analog Input
- 2 x** Push Terminal Unbalanced Female Analog Output
- 1 x** 1/8" / 3.5 mm TRS Unbalanced Female Analog Output

---

## Power

---

AC Input Power 100 to 240 VAC, 50/60 Hz

---

Power Consumption 60 W

---

## Environmental

---

Operating Temperature 32 to 104°F / 0 to 40°C

---

## General

---

Enclosure Material MDF

---

Mounting Points *None*

---

Dimensions (W x H x D) 5.5 x 8.1 x 7.1" / 14 x 20.6 x 18 cm  
(Each)

---

Weight 7.8 lb / 3.5 kg (Pair)

---

## Packaging Info

---

Package Weight 9.28 lb

---

Box Dimensions (LxWxH) 15.5 x 10.4 x 8"

---