

Mackie EM-91C Specs

Microphone

Form Factor	Stand/Boom Mount
-------------	------------------

Sound Field	Mono
-------------	------

Operating Principle	Pressure Gradient
---------------------	-------------------

Capsule	1 x Condenser
---------	----------------------

Polar Pattern	Cardioid
---------------	----------

Orientation	Side Address
-------------	--------------

Circuitry	Solid-State
-----------	-------------

Pad	<i>None</i>
-----	-------------

High-Pass Filter	<i>None</i>
------------------	-------------

Tone Adjustment	<i>None</i>
-----------------	-------------

Indicators	<i>None</i>
------------	-------------

On-Board Controls	<i>None</i>
-------------------	-------------

Windscreen

Built-In

Performance

Frequency Range 20 Hz to 18 kHz

Maximum SPL 134 dB SPL (1 kHz, 1% THD)

Impedance 150 Ohms \pm 30% at 1 kHz

Sensitivity -30 dBV/Pa at 1 kHz

Signal-to-Noise Ratio 78 dB

Equivalent Noise Level 16 dB A-Weighted

Connectivity

Output Connectors (Analog) **1 x** XLR 3-Pin Male (on Mic)

Headphone Connector *None*

Number of Conductors 2

Power

Operating Voltage 48 V

Physical

Color	Black
-------	-------

Mounting	Shockmount (with Included Hardware)
----------	-------------------------------------

Dimensions	ø: 1.9 x L: 6.1" / ø: 4.83 x L: 15.49 cm
------------	--

Weight	0.46 lb / 0.21 kg
--------	-------------------

Packaging Info

Package Weight	1.7 lb
----------------	--------

Box Dimensions (LxWxH)	13 x 10.5 x 5.7"
------------------------	------------------
