

# Mackie Thump Specs

## PA Speaker

---

Configuration	Active 2-Way
---------------	--------------

---

Total Power Capacity	1300 W
----------------------	--------

---

Amplifier Power Rating	<b>LF:</b> 1000 W <b>HF:</b> 300 W
------------------------	---

---

## Drivers

---

HF Driver	<b>1 x</b> 1.4" / 35.6 mm Titanium Dome Compression Driver
-----------	--

---

LF Driver	<b>1 x</b> 12" / 30.5 cm Woofer
-----------	---------------------------------

---

## Performance

---

Frequency Response	50 Hz to 23 kHz
--------------------	-----------------

---

Maximum SPL	126 dB
-------------	--------

---

Coverage Angle	90° H x 60° V
----------------	---------------

---

Protections

RMS, Thermal

---

## Connectivity

---

Audio I/O

**2 x** Combo XLR-1/4" Input  
**1 x** XLR Output

---

## Signal Processing

---

Dynamic Processing

Peak Limiter

---

Alignment Delay

Yes

---

## Power

---

AC Input Power

**Universal:**  
100 to 240 VAC, 50 / 60 Hz

---

AC Power Connector

**1 x** IEC

---

## Physical

---

Mounting

Pole Socket

---

Construction Material

Metal Grille, Polypropylene

---

Dimensions	14 x 14.1 x 24.2" / 35.6 x 35.8 x 61.5 cm
------------	---

---

Weight	35.5 lb / 16.1 kg
--------	-------------------

---

## Packaging Info

---

Package Weight	33.5 lb
----------------	---------

---

Box Dimensions (LxWxH)	27 x 17 x 17"
------------------------	---------------

---