

# Warm Audio WA-84 Specs

## Microphone

---

Form Factor	Stand/Boom Mount
-------------	------------------

---

Sound Field	Mono
-------------	------

---

Operating Principle	Pressure Gradient
---------------------	-------------------

---

Capsule	Condenser
---------	-----------

---

Polar Pattern	Cardioid
---------------	----------

---

Orientation	End Address
-------------	-------------

---

Circuitry	Solid-State
-----------	-------------

---

Pad	-10 dB
-----	--------

---

High-Pass Filter	<i>None</i>
------------------	-------------

---

Tone Adjustment	<i>None</i>
-----------------	-------------

---

On-Board Controls	Pad
-------------------	-----

---

Windscreen	Foam (Included)
------------	-----------------

---

## Performance

---

Frequency Range	20 Hz to 20 kHz
-----------------	-----------------

---

Maximum SPL	133 dB SPL
-------------	------------

---

Impedance	200 Ohms
-----------	----------

---

Load Impedance	1 Kilohms
----------------	-----------

---

Sensitivity	-39 dB at 1 kHz
-------------	-----------------

---

Dynamic Range	107 dB A-Weighted
---------------	-------------------

---

Signal-to-Noise Ratio	78 dB A-Weighted
-----------------------	------------------

---

Equivalent Noise Level	16 dB A-Weighted
------------------------	------------------

---

## Connectivity

---

Output Connectors (Analog)	<b>1 x</b> XLR 3-Pin Male (Locking, on Mic)
----------------------------	---

---

## Power

---

Operating Voltage	48 V (Phantom Power)
-------------------	----------------------

---

## Physical

---

Color	Nickel
-------	--------

---

Mounting	Mic Clip, Shockmount (Included)
----------	---------------------------------

---

Construction Material	Metal
-----------------------	-------

---

Dimensions	ø: 0.87 x L: 5.2" / ø: 22 x L: 132 mm
------------	---------------------------------------

---

Weight	4.3 oz / 122 g
--------	----------------

---

## Packaging Info

---

Package Weight	4.445 lb
----------------	----------

---

Box Dimensions (LxWxH)	13.6 x 11.2 x 4"
------------------------	------------------

---