

Specifications

MECHANICAL

Dimensions (LxWxH)

198 mm x 78 mm x 56 mm (7.8 in x 3.1 in x 2.2 in)

Weight

149 g (5.3 oz)

ELECTRICAL

Input Voltage

5 VDC + 0.25 V

Operating Power

600 mW (120 mA @ 5 V)

Standby Power

0.45 W (90mA @ 5 VDC)

Host System Interfaces

USB, RS232, Keyboard Wedge, IBM 46xx (RS485), OCIA, Laser Emulation, Light Pen Wand Emulation

ENVIRONMENTAL

Operating Temperature

0°C to 40°C (32°F to 104°F)

Storage Temperature

-40°C to 60°C (-40°F to 140°F)

Humidity

5% to 95% relative humidity, non-condensing

Drop

Designed to withstand 1.5 m (5 ft) drops

Environmental Sealing

Sealed to resist airborne particulate contaminants

Light Levels

4842 Lux

SCAN PERFORMANCE

Scan Pattern

Single scan line

Scan Speed

72 scan lines per second

Scan Angle

Horizontal: 50°

Symbol Contrast

35% minimum reflectance difference

Pitch, Skew

68°, 52°

Decode Capability

Reads standard 1D and GS1 DataBar symbologies

Warranty

5 year factory warranty