

Behringer B112D Specs

PA Speaker

Configuration	Active
---------------	--------

Total Power Capacity	1000 W
----------------------	--------

Amplifier Power Rating	LF: 700 W HF: 300 W
------------------------	--

Performance

Frequency Response	50 Hz to 20 kHz
--------------------	-----------------

Input Sensitivity	0 to -36 dBu
-------------------	--------------

Max Input Level	18 dBu
-----------------	--------

Gain Range	Up to 36 dB
------------	-------------

I/O Impedance	Input: 14 Kilohms
---------------	-----------------------------

Connectivity

Audio I/O	2 x Combo XLR-1/4" TRS Input 1 x XLR 3-Pin Output
USB	1 x USB Type-A (USB 3.0, Wireless Audio)
Wireless Connectivity	Proprietary Wireless
Wireless Range	262.5' / 80 m

Signal Processing

Crossover	2.8 kHz
EQ	HF Shelf: ±15 dB at 12 kHz LF Shelf: ±15 dB at 80 Hz
Dynamic Processing	Optical Limiter

Power

AC Input Power	120 VAC, 60 Hz (T 6.3 A H 250 V)
AC Power Connector	1 x IEC
Power Consumption	110 W (Max)

Physical

Dimensions 22.4 x 13.4 x 10.6" / 56.8 x 34.2 x 27 cm

Weight 27.1 lb / 12.3 kg

Packaging Info

Package Weight 31 lb

Box Dimensions (LxWxH) 26.3 x 17.4 x 14.7"
