

Behringer PPA2000BT Specs

Portable PA System

Speaker Configuration	2 x 2-Way Loudspeakers
Number of Input Channels	8 (4 x Mono, 2 x Stereo)
Amplifier Power Rating	2 x 1000 W Program (at 4 Ohms)

Speakers

Enclosure Type	Speaker: Bass-Reflex
HF Driver	1.35" / 34.2 mm Tweeter
LF Driver	10" / 25.4 cm Woofer

Signal Processing

EQ	1 x HF Shelf: ±15 dB at 12 kHz (per Channel) 1 x LF Shelf: ±15 dB at 80 Hz (per Channel) 1 x 7-Band Graphic (on Master)
Effects	100 x Preset (Factory)

Performance

Frequency Response 50 Hz to 22 kHz

Connectivity

Audio I/O

- 4 x** XLR 3-Pin Balanced Mic Input
- 4 x** 1/4" TRS Balanced/Unbalanced Input
- 6 x** 1/4" TS Unbalanced Line/Aux Input
- 1 x** 1/8" / 3.5 mm TRS Aux Input
- 2 x** Stereo RCA TS Unbalanced Line Input
- 1 x** Stereo RCA TS Line Output
- 1 x** 1/4" TRS Subwoofer Output
- 2 x** 1/4" TS Speaker Output

USB **1 x** USB Type-A (Wireless Audio) ⓘ

Bluetooth

Bluetooth Yes

Bluetooth Profiles A2DP 1.2

Pairing Manual

Bluetooth Channel 79

Frequency 2.4 GHz (2402 to 2480 MHz)

Bluetooth Power Class

2

Power

AC Input Power

Universal:

100 to 240 VAC, 60 Hz (T 8 A H 250 V)

Power Consumption

180 W

AC Power Connector

1 x IEC

Physical

Transport Options

1 x Handle (Top)

Mounting

1 x Pole Socket (Bottom) ⓘ

Construction Material

ABS

Dimensions

34.8 x 25.9 x 13.9" / 88.39 x 65.79 x 35.31 cm (Full Assembly)

Weight

68.3 lb / 30.98 kg (Full Assembly)

Packaging Info

Package Weight

81 lb

Box Dimensions (LxWxH)

36 x 28 x 16"
