

HANDHELD TRANSMITTER	.
RF Output Power	15mW (Max.)
Modulation Mode	FM (F3E)
Microphone Element	Dynamic, Cardioid
Dynamic Range	80dB
Frequency Response	50-12,000Hz
Current Consumption	≤130mA
Power Requirement	3V (2 × 1.5V AA Pencil Cells)
Controls	Transmitter ON/OFF Switch
Indication	Red LED for indicating transmitter ON
Dimensions	ø55 (L248) mm
Weight	180g (w/o battery)
TIE-CLIP TRANSMITTER	.
RF Output Power	15mW (Max.)
Modulation Mode	FM (F3E)
Microphone Element	Condenser, Omnidirectional
Dynamic Range	80dB
Frequency Response	80-15,000Hz
Current Consumption	≤130mA
Power Requirement	3V (2 × 1.5V AA Pencil Cells)
Controls	Transmitter ON/OFF Switch, Volume Control
Indication	Red LED for indicating transmitter ON
Dimensions	W67 x H32 x D95 mm
Weight	60g (w/o battery)
RECEIVER	.
Frequency Stability	± 0.005% Quartz Crystal Controlled
Receiving Method	Non-diversity
Audio Output	Channel 1: 0-55mV / 1kΩ, Channel 2: 0-55mV / 1kΩ Channel 1+2: 0-55mV / 1kΩ
Signal to Noise Ratio	> 80dB
Distortion	< 0.5%
Frequency Response	50-15,000Hz

Antenna	Telescopic
Power Requirement	240V AC 50Hz for AC adaptor (supplied along with)
Controls	Power On / Off Switch, Volume Control for Channel-1, Volume Control for Channel-2
Indications	Red LED for Power ON, Green LED for RF reception on Channel-1, Green LED for RF reception on Channel-2
Dimensions	W230 x H42 x D150 mm
Weight	353g
