

PRO25ax

A natural in high-SPL applications, the PRO 25ax is tailored for kick drum, percussion, brass, and other highly dynamic instruments. It delivers a warm low-frequency response with excellent presence. Its hypercardioid polar pattern improves isolation of the sound source, delivering superior off-axis rejection for maximum gain before feedback. The included isolation clamp offers versatile mounting options and effective dampening of mechanical noise.





Features

- Delivers a warm low-frequency response with excellent presence
- Hypercardioid polar pattern improves isolation of desired sound source
- Superior off-axis rejection for maximum gain before feedback
- Versatile mounting options and effective dampening of mechanical noise thanks to included AT8471 isolation clamp
- Rugged design and construction for reliable performance

Specifications

Microphones

Element

Dynamic

Polar Pattern

Hypercardioid

Frequency Response

30-12,000 Hz

Open Circuit Sensitivity

-54 dB (1.9 mV) re 1V at 1 Pa

Weight

8.1 oz (230 g)

Dimensions

4.45" (113.0 mm) long,
1.97" (50.0 mm) maximum diameter

Output Connector

Integral 3-pin XLRM-type

**Accessories
Included**

AT8471 isolation clamp for 5/8"-27 threaded stands; 5/8"-27 to 3/8"-16 threaded adapter; soft protective pouch
