

Specifications

Product type	PA loudspeaker
Type	passive
Low/mid driver dimensions	8 "
Woofer size	203.2 mm
Woofer magnet	Ferrite
Woofer brand	Custom-made
Woofer voice coil	2 "
Woofer voice coil (mm)	50.8 mm
Horn	BEM optimized CD Horn
HF driver dimensions	1 "
HF Driver Size	25.4 mm
HF driver magnet	Ferrite
HF driver brand	BMS
HF driver voice coil	1 "
HF Driver Voice Coil	25.4 mm
Dispersion (H x V)	90 x 50
Load rating (RMS)	250 W
Peak power	500 W
Frequency response	70 - 20000 Hz
SPL (1W/1m)	95 dB
Max. SPL	119 dB
Impedance	8 Ohm(s)
Protection circuits	HF Driver
Loudspeaker inputs	1
Speaker input connections	Speakon compatible

Loudspeaker outputs	1
Speaker output connections	Speakon compatible
Speakers per amplifier channel (DSP44/45K)	4
Cabinet material	12 mm Plywood
Cabinet surface	Polyurea
Cabinet construction	Bass Reflex
Width	270 mm
Height	457 mm
Depth	290 mm
Features	ergonomically shaped insert handles , M10 Thread for SuperClamp
Weight	9,9 kg