





SRT192BP



192 V



Extended-run battery systems provide flexible runtime to critical Smart-UPS applications.

Includes: Documentation CD, Installation guide, Warranty card



Technical Specifications

\sim					
()	П	Ť	n	u	T

Battery Output Voltage

Batteries & Runtime	
Battery type	Lead-acid battery
Battery mounting	Stand alone battery stack
Expected Battery Life (years)	3 - 5

Physical

RBC Quantity

Maximum Height	17.01inches (432MM, 43.2CM)
Maximum Width	5.12inches (130MM, 13.0CM)
Maximum Depth	26.88inches (683MM, 68.27CM)
Net Weight	200.62lbs. (91.0KG)
Shipping weight	223.77lbs. (101.5KG)
Shipping Height	16.54inches (420MM, 42.0CM)
Shipping Width	23.62inches (600MM, 60.0CM)
Shipping Depth	39.37inches (1000MM, 100.0CM)
Color	Black
Units per Pallet	1.0

Environmental

Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 (Non-condensing) %

Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 (Non-condensing) %
Storage Elevation	0 - 15000ft (0 - 4572meters)
Conformance	
Standard warranty	2 years repair or replace
Sustainable Offer Status	
RoHS	Compliant
Proposition 65 Warning	Available in Documentation tab

SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our Privacy Policy.

Email	
I am a	~

OK

WHO WE ARE CONNECT WITH US

About APC Press
Investor Relations APC Blog

Careers Schneider Electric Data Center Blog

Sustainability Contact Us

FIND A RESELLER

Zip/Postal Code	Find
-----------------	------

CATALOG KEYCODE

Enter Key Co	de	Go
--------------	----	----











Terms & Conditions

Data Privacy and Cookie Policy

2021, APC by Schneider Electric