

## Spec description

|                            |                                                                              |
|----------------------------|------------------------------------------------------------------------------|
| Recording media            | SD card (64MB to 2GB), SDHC card (4GB to 32GB)                               |
| Recording format           |                                                                              |
| WAV                        | 44.1k/48k/96k Hz, 16/24-bit                                                  |
| BWF                        | 44.1k/48k/96k Hz, 16/24-bit                                                  |
| Number of channels         | 4-channel (stereo x2)                                                        |
| Analog audio input         |                                                                              |
| 1/L, 2/R connectors        |                                                                              |
| Connector                  | XLR-3-31 (1:GND, 2:HOT, 3:COLD) / 1/4" (6.3mm) TRS standard jack             |
| Set to "MIC / MIC+PHANTOM" |                                                                              |
| Input impedance            | 2k $\Omega$                                                                  |
| Phantom power              | 48V $\pm$ 4V (10mA/CH) / 24V $\pm$ 4V (10mA/CH)                              |
| Maximum input level        | 0dBu                                                                         |
| Minimum input level        | -72dBu                                                                       |
| MIC input gain             | TRIM MAX                                                                     |
| LOW                        | +11dB                                                                        |
| MID                        | +36dB                                                                        |
| HIGH                       | +52dB                                                                        |
| HIGH+PLUS                  | +64dB                                                                        |
| Set to "LINE"              |                                                                              |
| Input impedance            | 10k $\Omega$ or more                                                         |
| Standard input level       | +4dBu                                                                        |
| Maximum input level        | +24dBu                                                                       |
| 3-4 connector              |                                                                              |
| Connector                  | 1/8" (3.5mm) stereo mini jack (this connector can be supplied plug-in power) |
| Input impedance            | 10k $\Omega$                                                                 |
| Maximum input level        | +10dBV                                                                       |
| Minimum input level        | -50dBV                                                                       |
| MIC input gain             | TRIM MAX                                                                     |
| LOW                        | +3dB                                                                         |

|                           |                                                                                                                                                                                          |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| HIGH                      | +26dB                                                                                                                                                                                    |
| HI + PLUS                 | +38dB                                                                                                                                                                                    |
| CAMERA IN connector       |                                                                                                                                                                                          |
| Connector                 | 1/8" (3.5mm) stereo mini jack                                                                                                                                                            |
| Input impedance           | 10k $\Omega$                                                                                                                                                                             |
| Standard input level      | -10dBV                                                                                                                                                                                   |
| Maximum input level       | +6dBV                                                                                                                                                                                    |
| Analog audio output       |                                                                                                                                                                                          |
| CAMERA OUT connector      |                                                                                                                                                                                          |
| Connector                 | 1/8" (3.5mm) stereo mini jack                                                                                                                                                            |
| Output impedance          | 200 $\Omega$                                                                                                                                                                             |
| Standard output level     | -50dBV                                                                                                                                                                                   |
| Maximum output level      | -30dBV                                                                                                                                                                                   |
| LINE OUT connector        |                                                                                                                                                                                          |
| Connector                 | 1/8" (3.5mm) stereo mini jack                                                                                                                                                            |
| Output impedance          | 200 $\Omega$                                                                                                                                                                             |
| Standard output level     | -10dBV                                                                                                                                                                                   |
| Maximum output level      | +10dBV                                                                                                                                                                                   |
| PHONES connector          |                                                                                                                                                                                          |
| Connector                 | 1/8" (3.5mm) stereo mini jack                                                                                                                                                            |
| Maximum output level      | 50mW + 50mW                                                                                                                                                                              |
| USB                       |                                                                                                                                                                                          |
| Connector                 | Mini-B type                                                                                                                                                                              |
| Format                    | USB2.0 HIGH SPEED mass storage class                                                                                                                                                     |
| REMOTE                    |                                                                                                                                                                                          |
| Connector                 | 2.5mm TRS jack                                                                                                                                                                           |
| Power                     | Four AA batteries (Alkaline or NI-MH),<br>USB bus power,<br>Dedicated AC adapter (TASCAM PS-P515U, sold separately),<br>Dedicated external battery pack (TASCAM BP-6AA, sold separately) |
| Power consumption         | 5.4W                                                                                                                                                                                     |
| Continuous operation time | 2ch WAV, 44.1kHz, 16-bit Rec, *All times are approximate.                                                                                                                                |
| DR-60D alone              |                                                                                                                                                                                          |

|                               |                                                                         |
|-------------------------------|-------------------------------------------------------------------------|
| Alkaline batteries (EVOLTA)   | 2-½ hours (Phantom ON)<br>4-½ hours (Phantom OFF)                       |
| NI-MH batteries (eneloop)     | 3-¾ hours (Phantom ON)<br>5 hours (Phantom OFF)                         |
| NI-MH batteries (eneloop pro) | 3-¾ hours (Phantom ON)<br>6 hours (Phantom OFF)                         |
| DR-60D with BP-6AA            |                                                                         |
| Alkaline batteries (EVOLTA)   | 5-½ hours (Phantom ON)<br>10-½ hours (Phantom OFF)                      |
| NI-MH batteries (eneloop)     | 7-½ hours (Phantom ON)<br>12 hours (Phantom OFF)                        |
| NI-MH batteries (eneloop pro) | 9-½ hours (Phantom ON)<br>14-½ hours (Phantom OFF)                      |
| Dimensions (W×H×D)            | 5.2" × 3.7" × 3.1" / 133 × 93.2 × 78 mm (with the top adapter attached) |
| Weight                        | 1.12 lbs. / 510 g (excluding batteries)                                 |
| Operating temperature         | 32°F to 104°F / 0°C to 40°C                                             |
| Standard accessories          | USB cable, warranty card, Owner's manual                                |