

Technical Data

[Jump to...](#)

Speaker Type	2-Way Active Speaker
---------------------	----------------------

Acoustical Data

[Jump to...](#)

Frequency Response [-10dB]	52 - 18.000 Hz
Max SPL	127 dB
HF	1" CD, 1.35"v.c
LF	12", 2.5" v.c.
Dispersion	90 Degree x 60 Degree
Crossover Frequency	1800 Hz (24 dB/oct.)

Amplifier

[Jump to...](#)

Amp Technology	Class D(LF)+Class AB(HF)
Power Peak (LF+HF)	800W

Processor

[Jump to...](#)

Controls	1xVolume, 1xslide switch mic/line
Indicators	Power on/Signal/Limiter LEDs
Controller	DSP 20/56 bit

AD/DA Converter	24 bit/ 48 Hz
Systems Presets	Playback, Flat, Bass Boost, Wedge
Limiter	Peak, RMS, Thermal
Advanced DSP Functions	Linear Phase FIR Filters

Input

[Jump to...](#)

Signal Input	1x Combo(XLR/Jack) Mic/Line 1xXLR/TRS
Bluetooth Input	1xBluetooth Receiver
SIGNAL Output	1xXLR Male (LINK/MIX)

Mechanics

[Jump to...](#)

Housing	Polypropylene
Handles	3 (2 on side 1 on top)
Angles Up	Monitor Use 45 Degree
Pole Mount	36mm, double positioning
Dimensions	14.37 x 24.50 x 13.46" (365 x 622 x 342mm)
Weight	36.37 lb (16.5kg)