

Comica Audio BOOMX-D MI RX Specs

Wireless Transmission	Digital 2.4 GHz
Diversity	Non-Diversity
RF Frequency Band	2400 to 2483.5 MHz
RF Channel Scanning	Auto-Scan
Max Operating Range	164' / 50 m (Line of Sight)
Max Systems per Setup	2
Latency	<20 ms (Maximum)

Receiver

Form Factor	Plug-In
Mounting Options	Plug-In
Antenna	1 x Internal
Number of Audio Channels	2
Audio I/O	1 x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output

Gain Range	0 to 12 dB
USB/Lightning Connectivity	1 x Lightning (Audio, Bus Power)
Approximate RF Sensitivity	-86 dBm
RF Output Power	10 mW
Power Requirements	Bus Power (Lightning)
Display & Indicators	1 x LCD (AF Level, Battery Status, Output Level)
Housing	Plastic
Operating Temperature	32 to 122°F / 0 to 50°C
Dimensions	1.3 x 0.5 x 2.8" / 33 x 13 x 70 mm
Weight	0.7 oz / 19 g

Packaging Info

Package Weight	0.065 lb
Box Dimensions (LxWxH)	3.7 x 2.25 x 0.7"