

Comica Audio CVM-WM300C Specs

System

Wireless Transmission	Analog UHF
Number of RF Channels	96
Included Transmitters	1 x Bodypack with Microphone
Diversity	Non-Diversity
RF Frequency Band	A: 520 to 548.5 MHz B: 550 to 578.5 MHz
RF Bandwidth	Up to 57 MHz
RF Channel Scanning	Auto-Scan
Max Operating Range	393.7' / 120 m (Line of Sight) 262.5' / 80 m (with Obstruction)
Max Systems per Setup	2
Latency	20 ms
Encryption	<i>None</i>

Modulation FM

Receiver

Form Factor Camera-Mount

Mounting Options Belt Clip, Shoe-Mount (with Included Hardware)

Antenna **2 x** 1/4 Wave External, Fixed (Top-Mount)

Number of Audio Channels 2

Audio I/O **1 x** 1/8" / 3.5 mm TRS Female Unbalanced Line Output (Lockable)
1 x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output (Lockable)

USB/Lightning Connectivity **1 x** Micro-USB (Charging)

Spurious Emission: < -60 dBc

Power Requirements Battery

Battery Type **1 x** Built-In Rechargeable (Included)

Internal Battery Capacity 2000 mAh

Approx. Battery Life 8 Hours

Display & Indicators **1 x** Backlit LCD (AF Level, Battery Status, Channel, Group, Level, Power, RF Level, Sync, Transmitter Battery Status)

2 x LED (Data Transmission, Sync)
1 x LED (Recharging)

Housing

Metal

Operating Temperature

32 to 122°F / 0 to 50°C

Storage Temperature

-4 to 140°F / -20 to 60°C

Dimensions

2.5 x 3.3 x 0.9" / 63.5 x 84 x 23 mm (without Antennas)

Transmitter

Form Factor

Bodypack

RF Output Power

10 / 30 mW

Audio I/O

1 x 1/8" / 3.5 mm TRS Female Unbalanced Input (Lockable)

Muting

Off/On Switch

Auto-Level Control

No

Signal Processing

High-Pass Filter:

Sync Method

IR

Antenna

1 x 1/4 Wave External, Fixed

Power Requirements	Battery
Battery Type	1 x Built-In Rechargeable (Included)
Internal Battery Capacity	2000 mAh
Approx. Battery Life	8 Hours
USB/Lightning Connectivity	1 x Micro-USB (Charging)
Display & Indicators	1 x Backlit LCD (Audio Level, Battery Status, Channel, Group, Mute, Power, RF Output Power) 1 x LED (Audio Level) 1 x LED (Sync) 1 x LED (Recharging)
Housing	Metal
Operating Temperature	32 to 122°F / 0 to 50°C
Storage Temperature	-4 to 140°F / -20 to 60°C
Dimensions	2.5 x 3.3 x 0.9" / 63.5 x 84 x 23 mm (without Antennas)

Microphone

Form Factor	Lavalier
Color	Black
Sound Field	Mono

Capsule	Electret Condenser
Polar Pattern	Omnidirectional
Frequency Range	30 Hz to 20 kHz
SNR	65 dB
Maximum SPL	100 dB SPL
Sensitivity	-35 dB
Output Connectors	1 x 1/8" / 3.5 mm TRS Male Unbalanced (Lockable)
Cable Length	3.94' / 1.2 m
