

AG06	AG03		
<b>Outline</b>			
<b>I/O</b>	<b>Phantom power</b>	+ 48 V	+ 48 V
<b>Input Channels</b>	<b>Mono[MIC/LINE]</b>	2 including HEADSET MIC (Plug-in Power)	1 including HEADSET MIC (Plug-in Power)
	<b>Stereo[LINE]</b>	2	1 including Guitar input (Mono)
	<b>AUX</b>	1	1
<b>Output Channels</b>	<b>STEREO OUT</b>	1	-
	<b>MONITOR OUT</b>	1	2
	<b>PHONES</b>	2 including HEADSET PHONES	2 including HEADSET PHONES
<b>Bus</b>		Stereo: 1	Stereo: 1
<b>Input Channel Function</b>	<b>PAD</b>	26 dB	26 dB
	<b>PEAK LED</b>	LED turns on when the signal reaches 3 dB below clipping level	LED turns on when the signal reaches 3 dB below clipping level
<b>On-board processors</b>	<b>DSP</b>	CH1: COMP / EQ, EFFECT (SPX Reverb) ; CH2: AMP SIM, EFFECT (SPX Reverb)	CH1: COMP / EQ, EFFECT (SPX Reverb)
<b>Level Meter</b>		USB Output Level; 2 x 2 point LED meter [PEAK, SIG]	USB Output Level; 2 x 2 point LED meter [PEAK, SIG]

<b>AG06</b>	<b>AG03</b>		
<b>USB</b>		USB Audio: 2 IN / 2 OUT, USB Audio Class 2.0 compliant, Sampling Frequency: Max 192 kHz, Bit Depth: 24-bit	USB Audio: 2 IN / 2 OUT, USB Audio Class 2.0 compliant, Sampling Frequency: Max 192 kHz, Bit Depth: 24-bit
<b>General specifications</b>			
<b>Power requirements</b>		DC 5 V, 500 mA	DC 5 V, 500 mA
<b>Power consumption</b>		Max. 2.5 W	Max. 2.5 W
<b>System Requirements</b>	<b>OS</b>	Windows 7 or later / Mac OS X 10.7 or later	Windows 7 or later / Mac OS X 10.7 or later
<b>Dimensions</b>	<b>W</b>	155 mm (6.1")	129 mm (5.1")
	<b>H</b>	63 mm (2.5")	63 mm (2.5")
	<b>D</b>	202 mm (8.0")	202 mm (8.0")
<b>Net weight</b>		1.0 kg (2.2 lbs)	0.8 kg (1.8 lbs)
<b>Options</b>		Foot Switch: FC5, Mic Stand Adaptor: BMS-10A	Foot Switch: FC5, Mic Stand Adaptor: BMS-10A
<b>Others</b>		Foot Switch: EFFECT Mute on / off, Operating Temperature: 0 to + 40 °C	Foot Switch: EFFECT Mute on / off, Operating Temperature: 0 to + 40 °C