



SRTG192XLBP4

Extended-run battery systems provide flexible runtime to critical Smart-UPS applications.

Includes: Installation guide, Warranty card

Technical Specifications

Output

Battery Output Voltage	192 V
------------------------	-------

Batteries & Runtime

Battery type	Lead-acid battery
Included Battery Modules	4
Battery mounting	Rack mount, Stand alone battery stack
Expected Battery Life (years)	3 - 5
RBC Quantity	2

Physical

Maximum Height	130MM, 13.0CM
Maximum Width	440MM, 44.0CM
Maximum Depth	683MM, 68.3CM
Net Weight	91.0KG
Shipping weight	101.5KG
Shipping Height	335MM, 33.5CM

APC



Color	Black
-------	-------

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (Non-condensing) %
Operating Elevation	0 - 2011.68meters

Storage Relative Humidity 0 - 95 (Non-condensing) %

Storage Elevation 0 - 15240meters

Conformance

Standard warranty 2 years

SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our [Privacy Policy](#).

Sign up

WHO WE ARE

[About APC](#)

[Investor Relations](#)

[Careers](#)

[Sustainability](#)

CONNECT WITH US

[Press](#)

[APC Blog](#)

[Schneider Electric Data Centre Blog](#)

[Contact Us](#)

FIND A RESELLER

CATALOG KEYCODE



[Terms & Conditions](#)

[Data Privacy and Cookie Policy](#)

[Change your cookie settings](#)

©2021, Schneider Electric