

Specifications

System Type	2-Way Premium Multi-Purpose Loudspeaker with 15" Differential Drive® Woofer and D2 Dual Driver
Components	1 x 2265H 15" Diameter Dual (3 in) Voice Coil, Neodymium Differential Drive®, Direct Cooled™ Transducer 1 x D2430K D2 Dual Diaphragm Dual Voice Coil Compression Driver
Coverage Pattern	90 x 50 degrees
Frequency Range (-10dB)	43 Hz - 21.5 kHz (short throw mode, free field) 42 Hz - 21.5 kHz (monitor mode, half-space)
Frequency Response (±3 dB)	59 Hz - 20 kHz (short throw mode, free field) 58 Hz - 20 kHz (monitor mode, half-space)
Sensitivity	98 dB LF, 108 dB HF
Nominal Impedance	LF = 8 ohms HF = 20 ohms
Transducer Power Rating (AES 2 hour)	1000W LF, 200W HF cont 4000W LF, 800W HF peak
Dimensions (H x W x D)	640.1mm x 457.2mm x 327.7mm (25.2in x 18in x 12.9in)
Net Weight (each)	22.9 kg (50.5 lbs)
Maximum Peak Output *2	134 dB (Preset: VTX F15 80)
LF Driver	1 x 15" Diameter Dual (3 in) Voice Coil, Neodymium Differential Drive®, Direct Cooled™ Transducer
HF Driver	1 x D2430K D2 Dual Diaphragm Dual Voice Coil Compression Driver
Enclosure	Symmetrical stage monitor (53 degree angle); 18 mm, 11-ply Baltic birch plywood; black DuraFlex™ finish; integral recessed handle
Suspension / Mounting	Integral pole mount socket (35 mm diameter); 16 x M10 mount points; Optional U-bracket and extension rod (SS5-BK) accessories available