

## Specifications

Frequency Range (-10dB)	55 Hz -20 kHz
Frequency Response ( $\pm 3$ dB)	70 Hz -18 kHz
System Power Rating	350 W (AES rated) 180 W / 360 W / 720 W (Continuous/Program/Peak) (IEC rated)
Impedance	8 ohms
Coverage Pattern	90° x 90°
Dimensions (H x W x D)	539.8 x 199.4 x 226.1mm (21.3 x 7.8 x 8.9in)
Net Weight (each)	11.0 kg (24.3 lb)
Maximum SPL (1m)	117 dB
System Sensitivity (1w @ 1m)	92 dB SPL
LF Driver	2 x JBL 226J, 165 mm (6.5 in) SFG™ driver with 50 mm (2 in) edge wound voice coil
Nominal LF Driver Impedance	8 Ohms
HF Driver	1 x 2414H 25 mm (1 in) exit compression driver, 25 mm (1 in) voice coil
Enclosure	12 mm and 15 mm exterior grade multi-ply hardwood plywood
Suspension Attachment	6 x M8 points; 1 top, 3 bottom, 2 rear. 4 x M6 rear for OmniMount® 30.0 or MultiMount® MM-022-BT, MM-024-BT, MM-020-CM.
Environmental	Mil-Std 810; IPx3 per IEC529. For higher environmental ratings, use WRC or WRX.