

Specifications

Frequency Range (-10dB)	40 Hz – 4.2 kHz
Frequency Response (± 3 dB)	47 Hz - 3.0 kHz
Transducer Power Rating (AES)	1000 W (4000 W peak), 2 hrs
System Power Rating	600 W (2400 W peak), 100 hrs
Maximum SPL (1m)	50 Hz – 125 Hz: 127 dB-SPL cont avg (133 dB peak) 125 Hz – 800 Hz: 126 dB-SPL cont avg (132 dB peak)
System Sensitivity (1w @ 1m)	50 Hz – 125 Hz: 97 dB 125 Hz – 800 Hz: 97 dB
Nominal Impedance	8 ohms
LF Driver	1 x JBL 2265H 380 mm (15 in) Differential Drive driver with 75 mm (3 in) dual voice coil
Enclosure	Trapezoidal with 15 degree side angles, 16 mm (5/8 in) exterior grade 11-ply Finnish birch plywood
Suspension Attachment	13 points (3 top, 3 bottom, 2 each side, 3 rear), M10 threaded hardware
Finish	Black DuraFlex™ finish. White available upon request.
Grille	Powder coated 14 gauge perforated steel, with acoustically transparent black foam backing.
Input Connector	NL4 Neutrik Speakon® and CE-compliant covered barrier strip terminals. Barrier terminals accept up to 5.2 sq mm (10 AWG) wire or max width 9 mm (.375 in) spade lugs. Speakon in parallel with barrier strip for loop-through.
Environmental	Mil-Std 810; IP-x3 per IEC529
Dimensions (H x W x D in vertical orientation)	548 x 561 x 657 mm (21.6 x 22.1 x 25.9 in)

Net Weight (each)	25.9 kg (57 lb)
Optional Accessories	M10 x 35 mm forged shoulder eyebolts with washers. Optional planar array frame kit. See AE Series Bracket Guide.
Nominal LF Driver Impedance	8 ohms