

Specifications

Frequency Range (-10dB)	35 Hz – 1 kHz
Frequency Response (± 3 dB)	43 Hz – 1 kHz
Transducer Power Rating (AES)	1000 W (4000 W peak), 2 hrs.
System Power Rating	700 W (2800 W peak), 100 hrs.
Maximum SPL (1m)	40 Hz - 300 Hz: 126 dB-SPL cont avg (132 dB peak)
System Sensitivity	40 Hz - 300 Hz: 96 dB-SPL, 1W (2.83V) @ 1m
Nominal Impedance	8 ohms
LF Driver	1 x 2263H, 305 mm (12 in) dia., 75 mm (3 in) Dual Coil Dual Gap neodymium Differential Drive® driver
Enclosure	Rectangular cabinet, 16 mm (5/8 in) exterior grade 11-ply birch plywood
Suspension Attachment	16 points (4 top, 4 bottom, 4 each side), M10 threaded hardware
Finish	Black DuraFlex™ finish. White available upon request.
Grille	Powder coated 14 gauge perforated steel, with acoustically transparent black foam backing.
Input Connector	NL4 Neutrik Speakon® and CE-compliant covered barrier strip terminals. Barrier terminals accept up to 5.2 sq mm (10 AWG) wire or max width 9 mm (.375 in) spade lugs. Speakon in parallel with barrier strip for loop-through.
Environmental	Mil-Std 810; IP-x3 per IEC529.
Dimensions (H x W x D in vertical orientation)	406 x 369 x 483 mm (16.0 x 14.5 x 19.0 in)
Net Weight	

Optional Accessories	M10 x 35 mm forged shoulder eyebolts with washers.
Nominal LF Driver Impedance	8 ohms