

## Specifications

Frequency Range (-10dB)	41 Hz to 1 kHz
Frequency Response ( $\pm 3$ dB)	49 Hz to 300 Hz
Transducer Power Rating (AES)	1600W (6400 W peak) 2 hrs
System Power Rating	P1200 W (4800 W peak), 100 hrs
Maximum SPL (1m)	128 dB-SPL cont avg (134 peak)
Input Modes	Drivers Parallel / Drivers Discrete
Nominal Impedance	4 ohms in parallel-drive mode
Sensitivity	116 dB-SPL
LF Driver	2 x JBL 2206H 300 mm (12 in) VGC drivers with 100 mm (4 in) voice coil with minimal power compression and low distortion
Enclosure	Trapezoidal with 15 degree side angles, 16 mm (5/8 in) exterior grade 11-ply
Waveguides	MF: PT-N64MF 600 x 600 mm (24 x 24 in) HF: PT-H64HF 300 x 300 mm (12 x 12 in)
Suspension Attachment	20 points (5 top, 5 bottom, 4 each side, 2 rear), M10 threaded hardware (eyebolts NOT included, see optional accessories).
Finish	Black DuraFlex™ finish. White (-WH) available upon request.
Optional Weather Resistant Versions	WRC for outdoor placement where the loudspeaker will be sheltered from direct exposure to the elements. WRX for direct exposure or extreme environments.
Grille	Powder coated 14 gauge perforated steel, zinc-phosphate dipped, foam backing (grille cloth backing on white units)
Input Connectors	Neutrik Speakon® NL4, plus CE-compliant covered barrier strip terminals. Barrier terminals accept up to 5.2 sq mm (10 AWG) wire or max width 9 mm (.375 in) spade lugs. Speakon in parallel with barrier

Environmental	Mil-Std 810; IP-x3 per IEC529. For higher environmental ratings, use WRC or WRX.
Dimensions (H x W x D in vertical orientation)	357 x 673 x 706 mm (14.1 x 26.5 x 27.8 in)
Net Weight (each)	36.4 kg (80 lb)
Optional Accessories	229-00009-01 kit of three M10 x 35 mm forged shoulder steel eyebolts.
Nominal LF Driver Impedance	4 ohms in parallel-drive mode 2 x 8 ohms in discrete drive mode