

性能

频率范围 (-10dB)	41 Hz to 17 kHz
Frequency Response (±3 dB)	49 Hz to 15 kHz
覆盖范围	/43: 40° x 30°/64: 60° x 40°/66: 60° x 60°/95: 90° x 50°
Crossover Modes	Tri-amp / Bi-amp (passive mid-high) switchable
Passive Crossover	6th order (36 dB/oct) Linkwitz-Riley HP & LP, 1.5 kHz
Transducer Power Rating (AES)	LF: 1600 W (6400 W peak), 2 hrs. 1200 W (4800 W peak), 100 hrs MF: 350 W (1400 W peak), 100 hrs HF: 75 W (300 W peak), 2 hrs
系统额定功率	LF: 1200 W (4800 W peak) MF/HF: 300 W (1200 W peak), 100 hrs
Maximum SPL (1m)	Tri-amp mode: LF: 128 dB-SPL cont avg (134 dB peak) MF: 134 dB-SPL cont avg (140 dB peak) HF: 133 dB-SPL cont avg (139 dB peak) Passive mode: 134 dB-SPL cont avg (140 dB peak)
System Sensitivity (1w @ 1m)	Passive Mode: 109 dB-SPL (mid/high section only)
低频驱动单元	2 x 2206H 300 mm (12 in) driver with 100 mm (4 in) voice coil
MF Driver	CMCD-82H cone midrange compression driver with integral 200 mm (8 in) diameter Differential Drive® dual 75 mm (3 in) voice coil driver
HF 驱动程序	2432H, 38 mm (1.5 in) exit compression driver with 75 mm (3 in) voice coil
Enclosure	Trapezoidal with 12.5 degree side angles, 16 mm (.625 in) exterior grade 11-ply Finnish birch plywood.
Suspension Attachment	20 points (5 top, 5 bottom, 4 each side, 2 rear), M10 threaded hardware (eyebolts NOT included, see optional accessories).
外观颜色	Black DuraFlex™ finish. White (-WH) available upon request.

Optional Weather Resistant Versions	WRC for outdoor placement where the loudspeaker will be sheltered from direct exposure to the elements. WRX for direct exposure or extreme environments, such as tropical or beach, or in areas with salt air, extreme high humidity or rapid changes in temperature.
网罩	Powder coated 14 gauge perforated steel, zinc-phosphate dipped, foam backing (grille cloth backing on white units)
输入接口	Neutrik Speakon® NL8, plus CE-compliant covered barrier strip terminals. Barrier terminals accept up to 5.2 sq mm (10 AWG) wire or max width 9 mm (.375 in) spade lugs. Speakon in parallel with barrier strip for loop through.
环境	Mil-Std 810; IP-x3 per IEC529
Dimensions (H x W x D in vertical orientation)	991 x 673 x 897 mm (39.0 x 26.5 x 35.3 in)
Net Weight (each)	77 kg (170 lb)
Optional Accessories	229-00009-01 kit of three M10 x 35 mm forged shoulder steel eyebolts
标称阻抗	4 ohms (2 x 8 ohms, internally wired in parallel)
Nominal LF Driver Impedance	4 ohms (2 x 8 ohms, internally wired in parallel)
Nominal MF Driver Impedance	8 ohms
Nominal HF Driver Impedance	8 ohms