

DMInteract®

From Visualization to Collaboration





DMInteract DM-950

1+1 Pocket 15 Multi Currency
Sorter With External Display

<https://dminteract.com>
<https://dubaimachines.com>

info@dubaimachines.com
+971-4-3360300

 @dubaimachines
 @dubaimachines

FEATURES:

- With UV, MG, IR, CIS (image) Counterfeit detection
- Auto currency identification and multi-currency mixed counting
- Accurate serial number recognition
- Half-note, double-note, chain-note detection
- Non-stop counting with reject pocket
- Face / Orientation / Version / Denomination notes sorting
- Add function, batch function, reporting and printing functions
- With touch control panel and 3.5 inch TFT display
- With USB interface, printer interface, external display interface
- Easy software upgrade via USB port
- Suitable for USD, EUR, GBP, RUB, CAD, AUD, AED, SYP, MXN, ARS, INR, IDR, THB, PKR, PHP, up to 60 currencies

SPECIFICATIONS:

- Hopper Capacity: Max 500 notes
- Stacker Capacity: Max 200 notes
- Reject Capacity: Max 100 notes
- Counting Speed: 800, 1000, 1200 notes/min for CNT mode | 800,1000 notes/min for MDC & SDC modes
- Dimensions: 288x270x245mm
- Power Supply: AC 100-240V 50-60Hz
- Size of Countable Notes: 50x110-90x190 mm
- Net Weight: 9.4 Kgs
- Gross Weight: 11.2 Kg
- Power Consumption: ≤80 W
- Connection Port: USB, RS-232, RJ-11

DMINTERACT DM-950 COMES WITH RECEIPT PRINTER



SPECIFICATIONS:

- Printing method: line thermal printing
- Printing paper width: 57.5±0.5mm
- Print density: 8 dots/mm, 384 dots/line.
- Printing speed: about 90mm/sec (the effective printing content of each line does not exceed 25%)
- Reliability: print head life: 100km
- Effective printing width: 48mm
- Interface form
- Serial port interface: DB 9 core socket (female type), supports XON/XOFF and RTS/CTS protocols.
Wave Bit rate: 1200~115200bps adjustable. Data structure: 1 start bit + 7 or 8 data bits + 1 bit stop bit.
- Barcode printing command: support UPCA, UPC-E, EAN-13 , EAN, CODE39, ITF25, CODABAR, CODE93, CODE128 barcode printing

Power Requirements

- DC12V±10%, 2A (one core).

Working Environment

- Operating temperature: 0~50°C
- Storage temperature: 20~60°C
- Operating relative humidity: 10-90%
- Machine Dimension: 184(L) X 129 (W) X 101(H) mm

DMINTERACT DM-950 SUPPORTED CURRENCIES (15 Max)

| | |
|--------------------|--|
| EUROPE | EURO Euro, GBP British Pound, BYN Belarus, RUB Russia, UAH Ukraine, RSD Serbia, KZT Kazakhstan, UZS Uzbekistan, MNT Mongolia, DKK Denmark, NOK Norway, SEK Sweden, MAD Morocco, CHF Switzerland, SCO Scotland, BAM Bosnia, TJS Tajikistan, HRK Croatia, PLN Poland, MKD Macedonia, BGN Bulgaria, CZK Czech, HUF Hungary, RON Romania, ALL Albania, GEL Georgian currency, AZN Azerbaijan, KGS Kyrgyzstan, MKD Macedonia, AMD Armenia |
| America | USD USA, BRL Brazil, MXN Mexico, ARS Argentina, COP Colombia, VEF Venezuela, PEN Peru, CAD Canada, CLP Chile, CRC Costa Rica, GTQ Guatemala, HNL Honduras, DOP Dominican Republic, BOB Bolivian currency, MDL El Salvador, NIO Nicaragua, PYG Paraguay, SRD Surinam |
| MIDDLE EAST | IQD Iraq, SAR Saudi Arabia, SYP Syria, AED United Arab Emirates, OMR Oman, LBP Lebanon, TRL Turkey, KWD Kuwait, EGP Egypt, YER Yemen, BHD Bahrain, QAR Qatar, JOD Jordanian, IRR Iran, ILS Israel, AFN Afghanistan |
| Asia | MYR Malaysia, IDR Indonesia, KRW Korea, JPY Japan, CNY China, INR Indian, THB Thailand, VND Vietnamese, TWD Taiwan, NPR Nepalese, MMK Myanmar, PHP Philippines, HKD Hong Kong, MOP Macau, LAK Laos, SGD Singapore, LKR Sri Lanka, MVR Maldives, KHR Cambodian Dollar, PKR Pakistan, AUD Australian Dollar, NZD New Zealand Dollar, BMD Brunei |
| Africa | GHS Ghana, ZAR South Africa, XOF West African Franc, XAF Central African Franc, CAF East African Franc, UYU Uruguay, NGN Nigeria, TZS Tanzania, ZWD Zimbabwe, AOA Angola, DZD Algeria, MGA Madagascar, ZMK Zambia, LYD Libya, BWP Botswana, TND Tunisian coin, NAD Namibia, KES Kenya, RWF Rwanda, UGS Uganda, MZN Mozambique, ETB Ethiopia, MUR Mauritius, GMD Gambia, CDF Congo, MWK Malawi |

