

Specifications

Print quality	
Maximum resolution	203 x 203 DPI
Maximum printing width	10.4 cm
Printing	
Print speed	152 mm/sec
Maximum resolution	203 x 203 DPI
Maximum printing width	10.4 cm
Print technology	Thermal transfer
Design	
Housing material	Metal
Display	LCD
Product colour	Black,White
Certification	IEC 60950, EN 55022 B, EN 55024, EN 61000-3-2, EN 61000-3-3, cTUVus, CE, FCC-B, ICES-003, VCCI, C-Tick, NOM, S Mark, CCC, GOST-R, KCC, BSMI
Display	
Display	LCD
Networking	
Wi-Fi	No
Ethernet LAN	Yes
Memory	
Internal memory	128 MB
Flash memory	128 MB
Ports & interfaces	
Standard interfaces	Ethernet
USB 2.0 ports quantity	1
RS-232 ports	1
Optional connectivity	Parallel,Wireless LAN
Connectivity technology	Wired

Wi-Fi	No
Ethernet LAN	Yes
Paper handling	
Media thickness (imperial)	0.003 - 0.01"
Media thickness	0.076 - 0.025 mm
Maximum media length (imperial)	157"
Maximum media length	3.99 m
Maximum label width	11.4 cm
Maximum label length	0.991 m
Performance	
Built-in barcodes	1D,2D,Code 128 (A/B/C),Code 39,Code 93,EAN13,EAN8,Industrial 2/5,Interleaved 2/5,MaxiCode,PDF417,POSTNET,TLC39,UPC-A,UPC-E
Ribbon width	11 cm
Ribbon length	450 m
Energy Star certified	Yes
Certification	IEC 60950, EN 55022 B, EN 55024, EN 61000-3-2, EN 61000-3-3, cTUVus, CE, FCC-B, ICES-003, VCCI, C-Tick, NOM, S Mark, CCC, GOST-R, KCC, BSMI
Power	
Power requirements	100 - 240 VAC, 47 - 63 Hz
Energy Star certified	Yes
Technical details	
Product colour	Black,White
Built-in barcodes	1D,2D,Code 128 (A/B/C),Code 39,Code 93,EAN13,EAN8,Industrial 2/5,Interleaved 2/5,MaxiCode,PDF417,POSTNET,TLC39,UPC-A,UPC-E
Ribbon width	11 cm
Ribbon length	450 m
Maximum label width	11.4 cm
Maximum	0.991 m

label length	
Certificates	
Energy Star certified	Yes
Certification	IEC 60950, EN 55022 B, EN 55024, EN 61000-3-2, EN 61000-3-3, cTUVus, CE, FCC-B, ICES-003, VCCI, C-Tick, NOM, S Mark, CCC, GOST-R, KCC, BSMI
Operational conditions	
Storage temperature (T-T)	-40 - 140 °F
Storage temperature (T-T)	-40 - 60 °C
Storage relative humidity (H-H)	5 - 85%
Operating temperature (T-T)	32 - 105 °F
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 85%
Weight & dimensions	
Width	242 mm
Depth	432 mm
Height	277 mm
Weight	9.1 kg