THROW RATIO		
1.2		
BRIGHTNESS (LUMENS)		
250		

RESOLUTION 854 x 480 THROW DISTANCE

40 in / 1.0 m

DISPLAY	
ТҮРЕ	RESOLUTION TYPE
DLP LED	WVGA (854x480)
RESOLUTION	BRIGHTNESS (LUMENS)
854 x 480	250
DISPLAY SIZE (IN.)	THROW DISTANCE
24 - 100 in. / 0.6 - 2.54 m	40 in / 1.0 m
THROW RATIO	KEYSTONE
1.2	Vertical (+/- 40°)
LENS	LIGHT SOURCE LIFE, NORMAL (HOURS)
Fixed Zoom	30000
COLOR DEPTH	DYNAMIC CONTRAST RATIO
1.07B Color (R/G/B 10bit)	120,000:1
ASPECT RATIO	
16:9	

VIDEO SIGNAL		
FREQUENCY HORIZONTAL	FREQUENCY VERTICAL	
15h~135kHz	23~120Hz	

COMPATIBILITY	
PC RESOLUTION (MAX)	PC RESOLUTION (MIN)
1920 x 1080	640 x 480
MAC® RESOLUTION (MAX)	MAC® RESOLUTION (MIN)
1920 x 1080	640 x 480

CONNECTOR		
USB 2.0 TYPE A	USB 3.1 TYPE C	
1	1	
CARD READER	3.5MM AUDIO OUT	
Micro SD	1	
HDMI 1.4		
1		

AUDIO	
INTERNAL SPEAKERS	
3W (x2)	

POWER	
VOLTAGE	CONSUMPTION (TYPICAL)
100-240 VAC	55W
STAND-BY	
<0.5W	

CONTROLS	
PHYSICAL CONTROLS	ON SCREEN DISPLAY
Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

OPERATING CONDITIONS	
TEMPERATURE	HUMIDITY (NON-CONDENSING)
32-104° F (0 - 40° C)	0-90%

WEIGHT (IMPERIAL)		
NET (LBS)	GROSS (LBS)	
1.7	3.7	

WEIGHT (METRIC)		
NET (KG)	GROSS (KG)	
0.8	1.7	

DIMENSIONS (IMPERIAL) (WXHXD)	
PACKAGING (IN.)	PHYSICAL (IN.)
16.0 x 9.2 x 15.0	5.7 x 1.6 x 5.0

DIMENSIONS (METRIC) (WXHXD)	
PACKAGING (MM)	PHYSICAL (MM)
406.0 x 233.0 x 380.0	146.0 x 40.0 x 126.0

GENERAL	
REGULATIONS	PACKAGE CONTENTS
FCC, cTUVus, ROHS, TUV-S, NOM, UL2054	M1 Projector, Power Cable, USB Type C Cable, Remote Control, Projector Case, Quick Start Guide
WARRANTY	RECYCLE/DISPOSAL
Three-year limited warranty on parts and labor, 1-year	Please dispose of in accordance with local, state or federal
limited warranty on the light source, 1st year free Express	laws.
Exchange® service. (One year Express Exchange Service	
requires product registration).	

DIMENSIONS 5.8 x 1.6 x 5.0 in / 148.0 x 40.5 x 126.0 mm





Projection Lens IR Remote Sensor 360° Smart Stand Focus Ring Micro SD DC In USB Type C HDMI 1.4 3.5mm Audio Out USB Type A Menu Controls Harman Kardon Speakers